ETS EUROPE BVBA
Herentalsebaan 406 D1.
2160 Wommelgem, Belgium
Tel: +32 3 227 28 58

E-Mail: info@ets-europe.be
www.ets-europe.be

CE

EU-Declaration of Performance
In accordance with Annex III of Regulation (EU) No.305/2011
(Construction Product Regulation)

For the product **"ECO RAPID DECO"**
No: ECO RAPID DECO

1. Unique identification code of the product-type:
EN 13813: CT–C40–F10–A12

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Batch number: See packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
EN 13813
Innovative self-leveling design floor. Hardens fast and tension-relieved with a layer thickness of 1 – 30 mm.

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):
ETS EUROPE BVBA
HERENTALSEBAAN 406 D1
2160 WOMMELGEM, BELGIUM

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):
Not Relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
Not relevant

9. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not relevant

ETS EUROPE BVBA
Herentalsebaan 406 D1.
2160 Wommelgem, Belgium
Tel: +32 3 227 28 58

E-Mail: info@ets-europe.be
www.ets-europe.be

9. Declared performance:

Essential Characteristic	**Performance**	**Harmonized technical specification**
Reaction to fire:	A1	EN 13813:2002
Release of corrosive substances:	CT	
Water permeability:	NPD	
Water vapour permeability:	NPD	
Compressive strength:	C40	
Flexural strength:	F10	
Wear resistance:	A12	
Sound insulation:	NPD	
Sound absorption:	NPD	
Thermal resistance:	NPD	
Chemical resistance:	ph> 4,5	
Dangerous substances:	none	

10. The performance of the product identified under point 1. and 2. is in conformity with the performance declared in section 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of the manufacturer by:

Jean-Luc De Potter, CEO
(Name and function)

de Potter Jean-Luc
(Signature)

[Wommelgem, 09.07.2020]
(Place and date of issue)